

Hose Protection

Hose Sleeve

Hose Sleeve

Safe Sleeve

MSHA + FRAS approved. Meets the requirements of ISO 3457, EN4413 and EN1299.
Recommended for use to protect personnel near by from hose burst (pin hole tested).
Recommended temperature range -40 °C to 120 °C- UV resistant.
Material - Polyester.



Part Number	Description	Roll Size (M)
MFS-17	SAFE SLEEVE MSHA. FRAS. 17MM I.D (30MM FLAT)	50M
MFS-23	SAFE SLEEVE MSHA. FRAS. 23MM I.D (40MM FLAT)	50M
MFS-27	SAFE SLEEVE MSHA. FRAS. 27MM I.D (45MM FLAT)	50M
MFS-31	SAFE SLEEVE MSHA. FRAS. 31MM I.D (51MM FLAT)	50M
MFS-40	SAFE SLEEVE MSHA. FRAS. 40MM I.D (65MM FLAT)	50M
MFS-47	SAFE SLEEVE MSHA. FRAS. 47MM I.D (76MM FLAT)	50M
MFS-55	SCUFF COVER MSHA 55MM ID (90MM FLAT) -50 TO 150 DEG	50M
MFS-60	SAFE SLEEVE MSHA. FRAS. 60MM I.D (97MM FLAT)	50M
MFS-78	SAFE SLEEVE MSHA. FRAS. 78MM I.D (125MM FLAT)	50M
MFS-109	SAFE SLEEVE MSHA 109MM ID (172MM FLAT) -40 TO 120 DEG	50M
MFS-126	SAFE SLEEVE MSHA 125MM ID (197MM FLAT) -40 TO 120 DEG	50M

Hose Sleeve

Fast Wrap

BOA Fastwrap sleeve is made from 100% PA6 textile sleeve with PU coating and hook and loop fasteners.
Comes in 25M rolls. Hook and loop design provides a quick and easy solution for bundling hose groups together. It can be used to protect cylinder rods from damage or contamination prolonging seal life. It can also be used for many other applications. Sleeve can be cut using standard scissors. A heat gun is useful for sealing the cut edge.

NOTE: Sold in full roll lengths only.



Part Number	Description	Roll Size (M)
FSTWRAP-25	FAST WRAP SLEEVE 25MM ID 25M ROLL QTY	25M
FSTWRAP-50	FASTWRAP SLEEVE 50MM I.D	25M
FSTWRAP-75	FAST WRAP SLEEVE 50MM ID 25M ROLL QTY	25M
FSTWRAP-100	FAST WRAP SLEEVE 100MM ID 25M ROLL QTY	25M
FSTWRAP-125	FAST WRAP SLEEVE 125MM ID 25M ROLL QTY	25M
FSTWRAP-150	FAST WRAP SLEEVE 150MM ID 25M ROLL QTY	25M
FSTWRAP-175	FAST WRAP SLEEVE 175MM ID 25M ROLL QTY	25M
FSTWRAP-200	FAST WRAP SLEEVE 200MM ID 25M ROLL QTY	25M

Can't find what you're looking for?

AU: 1800 40 30 40
NZ: 0800 20 20 20

Hose Protection

Hose Sleeve

Hose Sleeve

Fire Sleeve

BOA fire sleeve is the perfect choice for protecting industrial hydraulic hoses, pneumatic lines, fuel and oil hoses, brake hoses, wires and cables from exposure to high temperature heat or flames. Constructed from fibreglass yarn with a high grade silicone rubber coating.

Working temperature: 260° C(continuous), peak temperature 1650 °C



Part Number	Description	Roll Size (M)
FSRS015	FIRE SLEEVE RED SILICON 15MM I.D	20M
FSRS020	FIRE SLEEVE RED SILICON 20MM I.D	20M
FSR028	FIRE SLEEVE RED SILICON 28MM I.D	20M
FSRS035	FIRE SLEEVE RED SILICON 35MM I.D	20M
FSRS050	FIRE SLEEVE RED SILICON 50MM I.D	20M

Hose Sleeve

Spring Guard



Only sold by the roll

Part Number	I.D. (MM)	Pitch (MM)	Wire Size (MM)	Roll Size (M)
SG-17MM-10	17	3.0	1.8	10M
SG-22MM-10	22	4.0	1.8	10M
SG-25MM-10	25	4.0	1.8	10M
SG-32MM-10	32	6.0	2.0	10M
SG-36MM-10	36	6.0	2.0	10M
SG-41MM-10	41	8.0	2.5	5M
SG-44MM-10	44	8.0	2.5	5M
SG-51MM-10	51	8.0	3.0	5M
SG-54MM-10	54	10.0	3.0	5M
SG-59MM-10	59	10.0	3.0	5M
SG-62MM-10	62	12.0	3.0	5M

Hose Protection

Hose Sleeve

Hose Sleeve

Spiral Guard

General purpose flat spiral guard - made from High Density Polyethylene (HDPE).

Suitable for use -40°C to 80°C.

Oil resistant and UV resistant - Black.

Other colours and FRAS rated available on request.



MSHA +FRAS Approved

Part Number	I.D. (MM)	O.D. (MM)	Roll Size (M)
SPIRA12	9.5	12.5	50
SPIRA16	12.5	16.0	20
SPIRA20	16.0	20.0	20
SPIRA25	21.0	25.0	20
SPIRA32	27.0	32.0	20
SPIRA40	34.0	40.0	20
SPIRA50	44.0	50.0	20
SPIRA63	55.0	63.0	20
SPIRA75	66.0	75.0	20
SPIRA90	79.0	90.0	20
SPIRA110	99.0	110.0	12
SPIRA125	114.0	125.0	12

Hose Sleeve

FCC Crimp Rings



Part Number	I.D. (MM)
CR-27	27MM
CR-32	32MM
CR-39	39MM
CR-46	46MM
CR-59	59MM
CR-65	65MM
CR-82	82MM

Can't find what you're looking for?

AU: 1800 40 30 40
NZ: 0800 20 20 20